

## FEATURE

- 16CH AHD & Analog video Input, 8 CH HD IP video input
- Recording: 30fps/CH @ 720P, 15fps/CH @ 1080P, 20fps/CH @ 3Mp (For IPC)
- Playback: 8 CH simultaneously playback; HDMI 1080P output
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Cell phone: iPhone, Android; 2 x HDD
- COC (Control Over Coax)
- OSD Menu (Can Switch to Analog OSD via DVR)
- CVBS (BNC Output)
- P2P Function



## SPECIFICATION

Video & Audio	Video Input	16 x BNC ( HD AHD & Analog )
	IPC Input	8 x IP Camera
	Video Output	1 x HDMI : 1080P (1920 x 1080), 1 x VGA: 1080P (1920 x 1080), 1 x CVBS
	Audio In / Out	4 x RCA In / 1 x RCA Out
	2-Way Audio	Take up to 1CH audio input
Recording	Recording Resolution	960H, 720P: 1280x 720, 1080P: 1920 x 1080, 3Mp
	Frame Rate (fps)	720P @ 30fps/CH, 1080P @ 15fps/CH; 3Mp @ 20fps/CH (For IPC)
	Bit Rate	1M ~ 6Mbps
	Encode	VBR/CBR
	Record Mode	Manual, Timer, Motion
	Quality	6 Level
	File Manage	Lock, Unlock, Reserving Time
Alarm	Alarm	1 / 1 In/Out
	Mode	Motion, Video Loss
	Trigger Events	Record, PTZ Move, E-Mail, etc.
Playback	Playback	8CH
	Search Mode	Time, Motion, Single, or Multi-Channel
Network	Ethernet	RJ 45
	Protocol	TCP/IP, UDP, DHCP, DNS, PPPoE, DDNS
	Max User Access	10 Users online, dual stream
Storage	Internal HDD	2 x SATA
	External HDD	N/A
General	USB	2 x USB2.0, one for mouse & one for backup
	RS485	1 x RS485, Connect to PTZ or keyboard
	Power Supply & Consumption	DC 12V
	Working Environment	14°F ~ 122°F (-10°C ~ 50°C), 10%~90% (Humidity)
	Dimensions	16.9" x 11.8" x 2.2" ( W*D* H )