



FEATURE

- 32 CH HD TVI/AHD video input, 1080P / 960H / 720P / D1 recording
- Hybrid 32CH TVI/AHD video input / 32CH analog video input
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 8 CH simultaneously playback
- Search: time / calendar, events (sensor, motion)
- Backup via USB, network (DVD-RW (SATA) optional)
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively.
- Multi-user online simultaneously; HDMI 1080P output
- Authorization management, log review and device status review
- Supports PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Supports Andriod, iPhone



SPECIFICATION

Video	Input	BNC*32 , supports 1080P/720P TVI & AHD, 960H, D1 input
	Output	VGA*1 : 1080P(1920*1080) , HDMI*1 : 1080P(1920*1080)
Audio	Input & Output	RCA x 16 Input / RCA x 1 Output
	Dual-way audio	RCA*1
Record	Resolution	1080P(1920*1080), 720P(1280*720), 960H, D1
	Frame rate	720P : 800(PAL)/960(NTSC) , 1080P : 400(PAL)/480(NTSC)
	Bit Rate & Encode	1Mbps~6Mbps ; VBR/CBR
	Quality & Mode	6 level ; Manual, Timer, Motion, Sensor
	File manage	Lock, unlock, reserving time, redundancy
	Play	Playback & Search
Alarm	Function	Play, Pause, FF, FB; Digital zoom
	Mode	Sensor, Motion, Video Loss
	Input & Output	16CH Input / 4CH Output
Network	Triggering	Record, PTZ move, relay out, e-mail, etc
	Interface	RJ45 Giga ethernet
	Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS, E-mail
Cell phone	Others	10users online, dual stream
	OS	iPhone, Andriod
Port	Function	Multi-screen surveillance (for certain model) , record, snapshot, PTZ control, save the device list.
	HDD	SATA x 8
	RS485 & USB	RS485 *2 (PTZ & Keyboard) ; USB2.0 * 2 (Mouse & Backup)
Others	Power supply	AC(100~240V)
	Working Environment	32°F ~ 122°F (0°C~50°C), 10%~90% (Humidity)
	Dimensions	17" x 17.7" x 3.5" (W*D*H) (430mm*450mm*89mm)