

FEATURE

- Supports 32 CH 3MP@30fps or 1080P@30fps or 960P@30fps or 720P@30fps IP input
- Multi-mode recording: manual / timer / motion / sensor
- Playback : supports 4CH playback
- Search : calendar / time, events (sensor, motion)
- Express and flexible backup via USB, network or DVD-RW (SATA)
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- HDMI 1080P output, true high resolution display
- Supports PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Andriod. Compatible with 3G



SPECIFICATION

Video	Output	HDMI x 1 :1080P(1920*1080) ; VGA x 1:1080P(1920*1080)
IP input	Resolution	3MP / 1080P / 960P / 720P
	Frame rate	32CH 3Mp / 1080P / 960P / 720P @ 30fps
Audio	Input & Output	32 CH input ; 1 x RCA Output
	2-way audio	RCA*1
Record	Resolution	3MP: 2048 x 1536 / 1080P: 1920 x 1080 / 960P: 1280 x 960 / 720P: 1280 x 720 / D1: 704 x 576
	Frame rate	960fps(NTSC)
	Bit Rate:	256Kbps~12Mbps
	Encode & Quality	VBR/CBR ; 6 level
	Mode	Manual, Timer, Motion,Sensor
Playback	File manage	Lock, unlock, reserving time,
	Playback	4CH
	Search	Time/Calendar search,event(motion,external alarm)
	Smart Search	Apply different colors to display whether a channel in a period of time recording or not
Alarm	Function	Play, Pause, FF, FB;Digital zoom
	Mode	Sensor, Motion, Video Loss
	Input & Output	16 CH local input,support IPC alarm input ; 4CH Alarm Output
Network	Triggering	Record, alarm out, e-mail, etc
	Interface	GMAC *1
	Protocal	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS ,E-mail
Cell phone	Others	18 users online,dual stream
	OS	iPhone,Andriod
Port	Function	Multi-screen surveillance(for certain model),record,snapshot,PTZ control,save the device list
	HDD	SATAx8
	RS485	RS485*2, one for PTZ ,one for keyboard
	USB	USB3.0 x 1,USB2.0x1, one for mouse,another for USB backup device
Others	Remote controller	Yes
	Power supply	ATX (AC110~240V)
	Dimensions	16.9" (W) x 11.8" (D) x 3.5" (H) (430 x 450 x 89mm)
	Working Environment	14°F ~ 122°F (-10~55°C) , 10%~90% (Humidity)