

- (3 in 1) Tri-Brid HD *E Model Camera
- Compatible with HD-AHD, HD-TVI, & Analog Cameras
- 1/3" 2.4Mp HD Sensor with 3.7mm Pinhole Lens
- 1920(H) x 1080(V) Effective Pixels, Max. 30fps @ NTSC
- 18 Hidden IR with 0Lux, 0.01Lux @ F1.2 (AGC On)
- Transmitting Control Signal via Coaxial Cable
- High-speed & Long-distance Real Time Transmission
- ICR auto switches between Day & Nigh time



***E Model Features**

- On-Screen Display (OSD) Menu
- Control over Coax (CoC) Protocols
- Frontlight Compensation (FLC)
- Backlight Compensation (BLC)
- NTSC & PAL Video Signals

CAMERA	Image Sensor	1/3" 2.4Mp HD Sensor
	Effective Pixels	1920 (H) x 1080 (V)
	Electronic Shutter	1/50-1/100,000Sec (PAL) & 1/60-1/100,000Sec (NTSC)
	S/N Ratio	≥ 48 dB
	Video Output	Composite Signal (1.0Vp-p, 75Ω)
	Video Frame Rate	30fps @ 1080P
	Audio Output	Max. 2Vp-p
	Lens	3.7mm Pinhole Lens
	Lens Types	Manual
	Lens Mount Types	M12
	IR Lens	18 Hidden
	IR Distance	10 ~ 15m (33 ~ 49ft)
	Min. Illumination	0 Lux (IR On), 0.01 Lux @ F1.2 (AGC On)
FUNCTIONS	Automatic Gain Control (AGC)	Yes
	Day-Night Switch	ICR Auto Switch
	WDR	Digital WDR
	DNR	2D
	OSD Menu	Yes (Compatible with Analog-mode)
	Control over Coax (CoC)	Yes
	Remote Monitoring	IE Browsing, Central Monitoring System (CMS)
	Transmission Distance	Over 500m via 75-3 Coaxial Cable
	Alarm	No
Waterproof	No	
OTHERS	Power Supply	DC 12V ± 10%
	Power Consumption	500 mA
	Working Environment	-22°F ~ 140°F (-30°C ~ 60°C)
	Storage Environment	-40°F ~ 176°F (-40°C ~ 80°C); Humidity: Indoor 85% RH (Non-Condensation)
	Dimension	4.7" x 2.7" (120 x 69mm)
	Weight	0.26lbs (0.12kg)