



- (3 in 1) Tri-Brid HD \*E Model Camera
- Compatible with HD-AHD, HD-TVI, & Analog
- 1/3" 2.4Mp HD Sensor with 2.8mm / 3.6mm Fixed Lens
- 1920(H) x 1080(V) Effective Pixels, Max. 30fps @ 1080p
- 24 IR with 0Lux, 0.01Lux @ F1.2 (AGC On)
- Transmitting Control Signal via Coaxial Cable
- High-speed & Long-distance Real Time Transmission
- ICR auto switches between Day & Nigh time

**\*E Model Features**  
 On-Screen Display (OSD) Menu  
 Control over Coax (CoC) Protocols  
 Frontlight Compensation (FLC)  
 Backlight Compensation (BLC)  
 NTSC & PAL Video Signals

CAMERA	Image Sensor	1/3" 2.4Mp HD Sensor
	Effective Pixels	1920 (H) x 1080 (V)
	Electronic Shutter	1/50-1/100,000Sec (PAL) & 1/60-1/100,000Sec (NTSC)
	Lens	Two Models: 2.8mm Fixed Lens or 3.6mm Fixed Lens
	Lens Mount Types	M12
	IR Lens	24 IR
	IR Distance	49 ~ 66ft (15 ~ 20m)
	Min. Illumination	0 Lux (IR On), 0.01 Lux @ F1.2 (AGC On)
IMAGE	Resolution	1080P (1920*1080) / 720P (1280*720) / D1 / CIF / 480*240
	Encode Mode	VBR / CBR
	Image Quality	5 Levels VBR; Adjustable under CBR
	Bitrate	64 Kbps ~ 8 Mbps
FUNCTIONS	Network Interfaces	RJ45
	Automatic Gain Control (AGC)	Yes
	Day-Night Switch	ICR Auto Switch / B&W / Color
	WDR	No
	DNR	2D / 3D Noise Reduction
	OSD Menu	Yes (Compatible with Analog-mode)
	Control over Coax (CoC)	Yes
	Remote Monitoring	IE Browsing, Central Monitoring System (CMS)
	Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Alarm	No
	Waterproof	IP66
OTHERS	Power Supply	DC 12V ± 10%
	Power Consumption	500 mA
	Working Environment	-22°F ~ 140°F (-30°C ~ 60°C)
	Storage Humidity	Indoor 85% RH (Non-Condensation)
	Dimension	3.9" (R) x 2.8" (H) (99 x 73 mm)
	Weight	0.77lbs (0.35kg)