


## H.265 4MP HD-IP IR Dome Camera



## Features

- 1/3" Panasonic Sensor
- 4MP Camera
- Max. resolution: 2688(H) × 1520(V)
- ICR auto switch, true day / night
- 3D DNR
- Supports smart analysis of valuables watching, perimeter and abnormal video signal detection
- Supports defogging, BLC, digital image stabilization and defect correction to fit different needs
- Supports CVBS
- Support smart phone, iPad, remote monitoring

## Specifications

Model	IP-5IRD3002-2.8
<b>Camera</b>	
Image Sensor	1 / 3" CMOS
Effective Pixels	2688(H) × 1520(V)
Electronic Shutter	1/25s~1/100000s
Min. Illumination	Color:0.05lux@F1.2,AGC ON B/W:0lux with IR
Lens	3.6mm Fixed Lens
Lens Angle	Horizontal: 50°
WDR	WDR
BLC	Yes
DNR	2D/3D DNR
<b>Image</b>	
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A/G.711U
Bit-rate	64Kbps ~ 10Mbps
Encode Mode	VBR/CBR
Image Quality	Five Levels under VBR: Freely adjustable under CBR
Resolution	4MP ( 2560×1440 ), 3MP ( 2304×1296 ), 1080P ( 1920×1080 ), 720P ( 1280×720 ), D1, CIF, 480×240
Video Frame Rate	60Hz : 4MP ( 1 ~ 30fps ) / 3MP ( 1 ~ 30fps ) / 1080P ( 1 ~ 30fps ) / 720P ( 1~30fps ) / D1 (1~30fps) / CIF (1~30fps) 50Hz : 4MP ( 1 ~ 25fps ) / 3MP ( 1 ~ 25fps ) / 1080P ( 1 ~ 25fps ) / 720P ( 1 ~ 25fps )
Image Setting	ROI, Saturation, Brightness, Hue, Contrast,WDR, Sharpness, DNR, etc
<b>Port</b>	
Network	RJ45
Video output	CVBS (BNC × 1)
Audio	one-way audio (MIC IN × 1)
Card Storage	N/A
RS485	N/A
Alarm In / Out	N/A
<b>Function</b>	
Remote Monitoring	Browser, CMS ,mobile app
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 online users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	network remote storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA/OSC/AVD
Day & Night	ICR
IR Distance	20~30m
IR LED - count	2 (array led 28mil)
Water-proof	IP66
<b>Others</b>	
Angle Adjustment	horizontal:0°~360°, vertical:0°~90°, rotation:0°~360°
Power Supply	DC 12V/PoE
Power Consumption	< 2.5W (IR Off) / < 5W (IR On)
Working Environment	-20°C ~ 50°C , 10% ~ 90% Humidity
Dimension & Weight	Φ87mm×219mm / ≈609g