

NC304-TD

4MP WDR Fixed DomeNetwork Camera



- Up to 4megapixel high resolution
- Full HD1080p video
- Dual video streams
- 2.8mm/4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- 3-axis adjustment

- DC12V & PoE
- Support H.264+
- Up to 30m IR range
- IP66 weather-proof protection
- IK08(-W model)/IK10(non -W model)
- Support on-board storage, upto 64GB

Camera Accessories



Inclined ceiling mount
DS-1259ZJ



Wall moun
DS-1272ZJ-110



Wall mount + Junction Box
DS-1272ZJ-110B



Pendant mount
DS-1271ZJ-110B



Junction Box
DS-1280ZJ-DM18



Corner mount
DS-1276ZJ



Vertical Pole mount
DS-1275ZJ



Rain-proof Cap
DS-1250ZJ



NC304-TD-2.8 / 4MM

4MP WDR Fixed Dome Network Camera



Specification

| | |
|-----------------------------|---|
| Camera | |
| Image Sensor | 1/3" Progressive Scan CMOS |
| Min. Illumination | 0.01Lux @ (F1.2, AGC ON) ,0 Luxwith IR |
| Shutter Speed | 1/3 s to 1/10,000 s |
| Lens | 2.8mm, 4mm @ F2.0, 6mm |
| Lens Mount | M12 |
| Day & Night | IR cut filter with auto switch |
| DNR | 3D DNR |
| Wide Dynamic Range | 120dB |
| P&T rotation | Pan: 0° ~355°, Tilt: 0° ~75°, Rotation: 0° ~355° |
| Compression Standard | |
| Video Compression | H.264 / MJPEG / H.264+ |
| H.264 Type | Main Profile |
| Video Bit Rate | 32 Kbps ~ 16Mbps |
| Dual streams | Support |
| Image | |
| Max. Resolution | 2688×1520 |
| Frame Rate | 50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720) 60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720) |
| Image Setting | Rotate Mode, Saturation, Brightness, Contrast, Sharpnessadjustable by client software or web browser |
| BLC | Support, zone configurable |
| ROI Codec | Support |
| Network | |
| Network Storage | NAS (Support NFS,SMB/CIFS), ANR |
| Alarm Trigger | Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception |
| Protocols | TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour |
| General | One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access |
| Standard | ONVIF (PROFILE S,PROFILE G),PSIA,CGI,ISAPI |
| Interface | |
| Communication Interface | 1 RJ45 10M/100M Ethernet port |
| On-board storage | Built GB128icro SD/SDHC/SDXC slot, up to in M- |
| Alarm interface | 1x alarm I/O *only for-S models |
| Audio interface | 1x audio I/O *only for-S models |
| Reset | Yes |

Design and specifications are subject to change without notice.