

FEATURE

- Powerful 20x optical zoom, 1/3" 2 MP Sony 222 CMOS
- HD-TVI Lossless video output
- Max. 25/30fps@1080p resolution
- DWDR, Defog, Day/Night(ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC
- OSD menu with humanized design, easy for operation
- Max 200°/s pan speed, 360° endless rotation
- Up to 128 presets, 4 auto scan, 4 tour, 4 pattern, clock functions
- AC24V/DC12V, IP66
- New array IR LEDs up to 120m, constant control, lower consumption and longer works life for IR lights



SPECIFICATION

| | | |
|-----------|---------------------|--|
| Camera | Image Sensor | 1/3" 2Mp Sony 222 CMOS Sensor |
| | Effective Pixels | 1920 x 1080p |
| | Mini. Illumination | Color: 0.1 Lux; W/B: 0.01 Lux |
| | Video Output | Female BNC |
| | Baud Rate | 2400 / 4800 / 9600 / 19200 bps |
| | WDR | DWDR |
| | OSD Menu | Yes |
| PTZ | Zoom | 20X Optical, f=4.7-94mm, |
| | Preset Speed | 200°/S |
| | Rotation | Continuously 360° ; tilt 0~90° |
| | Speed Setup | Pan (0.2°~200°/s) / Tilt (0.2°~100°/s) |
| | Auto Flip | Yes |
| | Power Up Action | Auto restore to previous PTZ and lens status after power failure |
| | Idle Motion | Activate Preset/Pan/Scan/Tour/Pattern if there is no command in the specified period |
| | Scan | 355° programmable · 4 scans |
| | Time Task | Auto activation of Preset/Pan/Scan/Tour/Pattern by preset-time |
| | Pattern | 4 patterns, time and speed can be set |
| Recording | Protocol | Pelco D/P auto recognized |
| | Display Zone | 8 programmable zones with titles |
| | Frame Rate (fps) | 30fps |
| Others | RS485 | RS485 & Coaxial support |
| | Power Supply | AC24V/DC12V |
| | Protection | IP66, 4000v lightning-proof, surge-proof |
| | Working Environment | -40°C ~ +60°C, Humidity: 0~95% (Non-condensation) |
| | Weight | 6Kg |